

ARC

Asphalt Research Consortium

ARC Update on Warm Mix Research

By Hussain Bahia

Presented to

Manitoba, Infrastructure and Transportation

Materials Engineering Branch

Central Lab, 1181 Portage Avenue Annex

Winnipeg, Manitoba

March 17, 2009


ARC Subtask E1c-1:

Effect of WMA Additives

- **Progress Update**
 - **Binder Properties**
 - **Viscosity**
 - **Performance Grade**
 - **Mixture Workability**
 - **Compaction Curves**
 - **Workability Indices**


Effect on Viscosity: PG64-22

PG64-22 Viscosity vs. Shear Rate




Effect on Viscosity: PG76-22


PG76-22 Viscosity vs. Shear Rate



Effects of WMA Additives: HT PG Grade ($G^*/\sin\delta$)




2% Sasobit - One Grade Bump



0.5% Surfactant - One Grade Lower

Effects of WMA Additives: HT PG Grade (MSCR)


MSCR J_{nr} Results - RTFO Binder




➤ Sasobit shows much higher stress sensitivity

Effects of WMA Additives: LT PG Grade

Temperature -12°C



Temperature -12°C



Mixture Workability

— Mix Design

- **NMAS: 19.0 mm/Gradation: Fine /AC: 5.4%**


— Binder Grades

- **PG64-22-and polymer-modified PG76-22**

— Evaluation Criteria


- **Compaction Curves and Air Voids**
- **Workability indices**
 - > **Construction Densification Index (CDI)**
 - > **Construction Force Index (CFI)**

Mixture Workability - CDI



- **CDI Based on Compaction Curves:**
 - **Area under the %Gmm vs. Gyration Curve from N_{ini} – 92% Gmm. Densification after paver to field compaction.**
 - **Lower CDI relates to better workability.**


Mixture Workability - CFI



- **CFI Based on Force Measured by PDA Plate:**
 - Pressure Distribution Analyzer (PDA) allow for calculation of resistive forces in the mix during compaction (w)
 - CFI calculated as the area under the Resistive Force (w) vs. Gyration curve


Mixture Workability – 600KPa

Densification Curves for PG76: 600 kPa, 110 C




- **No noticeable effects of WMA Additives.**

Densification Curves for PG76: 600 kPa, 90 C




- **Additives allow mixes at 90°C to attain density of control mix at 135°C.**

Mixture Workability – 300KPa




Mixture Workability – CDI- 600KPa

PG 76-22 Voids Analysis - 600 kPa, N=21 Gyration




- Little difference between mixes until 90°C compaction temperatures.
- WMA has significantly lower % Air Voids.

PG76: CDI vs. Temperature - 600 kPa




- CDI shows similar trends. WMA much more workable at 90°C than HMA.
- CDI of WMA 66% lower.

Mixture Workability – CDI- 300KPa



Mixture Workability - CFI

PG76: CFI vs. Temperature - 600 kPa



- **Construction Force Index**

- **Force measurements are consistent – WMA additive requires less force to reach the same level of compaction.**

Moving Forward – Binder

Binder	PG Grade	η	Adhesion / Cohesion	Rutting (OB & RTFO)		Fatigue (PAV)		Low Temperature (PAV)	
		ZSV	UW-Madison Tack Test	G*/sin δ - (HT °C)	MSCR (HT°C)	G* sin δ (IT °C)	BYET (IT °C)	BBR (LT+10°C)	SENB (LT+10°C)
Neat L	64-22	✓	X	✓	✓	✓	✓	✓	X
Neat H	76-22	✓	X	✓	✓	✓	✓	✓	X
Neat L+ 2% Sasobit	70-22	✓	X	✓	✓	✓	✓	✓	X
Neat H+ 2% Sasobit	76-22	✓	X	✓	✓	✓	✓	✓	X
Neat L + Surfactant	X	✓	X	✓	✓	X	X	✓	X
Neat H + Surfactant	X	✓	X	✓	✓	X	X	✓	X
Neat L Foamed	X	X	X	X	X	X	X	X	X
Neat H Foamed	X	X	X	X	X	X	X	X	X

✓ = Test completed

X = Test is planned

Moving Forward – Workability


			Binder									
			PG64-22					PG76-22				
Gradation	Pressure [kPa]	Comp. Temp. [°C]	Control	Mineral Based Additive	Surfactant	Foaming	Sasobit	Control	Mineral-Based Additive	Surfactant	Foaming	Sasobit
19mm Fine	600	135	✓	✓	X	X	X	✓	✓	X	X	X
		110	✓	✓	✓	X	X	✓	✓	✓	X	X
		90	✓	✓	✓	X	X	✓	✓	✓	X	X
	300	135	✓	✓	X	X	X	✓	✓	X	X	X
		110	✓	✓	✓	X	X	✓	✓	✓	X	X
		90	✓	✓	✓	X	X	✓	✓	✓	X	X
19mm Coarse	600	135	X	X	X	X	X	X	X	X	X	X
		110	X	X	X	X	X	X	X	X	X	X
		90	X	X	X	X	X	X	X	X	X	X
	300	135	X	X	X	X	X	X	X	X	X	X
		110	X	X	X	X	X	X	X	X	X	X
		90	X	X	X	X	X	X	X	X	X	X

✓ = Test completed

X = Test is planned

Testing of Field Mixtures

Field Projects in WI – 2008



Field Mixes – with RAP

Aggregate	HMA - Design	HMA - UW	WMA - 30% QC	WMA-40%
Compaction Temp (F)	275	275	215	221
Nini - 7	91.2%	90.4%	92.0%	93.8%
Ndes - 60	96.1%	95.4%	97.0%	98.3%
Nmax- 75	96.6%	95.8%	N/A*	N/A*
VMA	14.10	12.86	12.30	11.00
*WMA QC samples were compacted to Ndes.				

Summary / Wish List

- **WMA works at lower temps**
 - Density is not a good measure
 - Better use densification indicators
- **Project should include true control**
 - HMA @ same temps as WMA
 - Enough materials
 - Good recording of temp, roller passes and sampling

Thank you !

- **For giving us the opportunity**
- **For the warm reception to talk about warm asphalt**
- **Getting us to visit Winnipeg during our spring break!**